

Application and Product Selection Guide

Page No.	Types of Anchors	Fastening Base Material						Application Criteria						Program			
		Concrete	Hard Natural Stone	Soft Natural Stone	Solid/Hollow Brick	Grout Filled Block	Hollow Concrete Block	Wood/Metal Gypsum/Plastic Foam Ins	In-place (through) Fastening	Immediate Loading	Flush Surface Removing	Dynamic Loading	Temp Resistant	Materials	Versions	Characteristics	
HEAVY DUTY																	
28	Liquid Roc 300 Capsule	●	○			○									Polyester Resin Benzoyl Peroxide Hardener Quartz Sand	Threaded Rod Rebar Smooth Dowel (Chamfer Cut)	Mixes in hole with use of rotary hammer only
29	Liquid Roc 300 Hammer Capsule	●	○			○									Polyester Resin Benzoyl Peroxide Hardener Quartz Sand	Threaded Rod Rebar (Straight Cut)	Mixes in hole by driving a rod with a hammer
31	Liquid Roc 300 Twin Tube	●	●	●	●	●	○								Polyester Resin Benzoyl Peroxide Hardener	Threaded Rod Rebar Smooth Dowel (Straight Cut)	Bonds to Hollow or Solid Masonry
30	Liquid Roc 300 Pouch	●	○	○											Polyester Resin Benzoyl Peroxide Hardener	Threaded Rod Rebar Smooth Dowel (Straight Cut)	Bonds to Solid Masonry
32-34	Liquid Roc 500 Single/Twin Tube, Low Odor	●	●	●	○	●									Amine Base Epoxy	Threaded Rod Rebar Smooth Dowel (Straight Cut)	Bonds to Solid Masonry Low Odor
33	Liquid Roc 700 Single/Twin Tube	●	●	●	●	●	○								Acrylic Base, Benzoyl Peroxide Hardener	Threaded Rod Rebar Smooth Dowel (Straight Cut)	Bonds to Hollow or Solid Masonry

KEY ● VERY SUITABLE ○ MAY BE SUITABLE PER APPLICATION