

Plastic Screw Anchor



Available materials

- Polypropylene

Features/Advantages

- Light loads only under dead or slightly variable conditions in all atmospheric conditions
- Accepts both wood and sheet metal screws
- Fast, easy installation

Order Detail

Order Code	Dia. & Length	Hole Dia.	Screw Size	Ultimate Tension in Lbs.*				Box Qty.	Master Qty.
				8x1 1/4	10x1 1/4	10x1 1/2	12x1 1/2		
8450	3/16 x 7/8	3/16"	8-10	115	385	—	—	100	3,000
8451	3/16 x 7/8	3/16"	8-10	115	385	—	—	1,000	5,000
8460	1/4 x 1	1/4"	10-12	—	—	195	543	100	3,000
8461	1/4 x 1	1/4"	10-12	—	—	195	543	1,000	3,000
8430	5/16 x 1 3/8	5/16"	14-16	n/a	n/a	n/a	n/a	100	1,200
Kits With Drill And Screws									
**84501	3/16 x 7/8	3/16"	8	115	385	—	—	1	12
**84601	1/4 x 1	1/4"	10	—	—	195	543	1	12

*Tested in concrete block.

**Includes Carbide Drill Bit and 100 Anchors and Screws

Installation

- 1 Drill recommended diameter hole slightly deeper than length of anchor. Clean hole of debris.
- 2 Insert plastic anchor into hole.
- 3 Place fixture over anchor and insert screw through fixture and into anchor. Tighten.

